

**Sikorsky S-92
S/N 92009
Approx 820 TT**



Available Immediately!

GENERAL SPECIFICATIONS

Standard S-92 Aircraft featuring:

Two General Electric CT7-8 Turbo-shaft Engines w/Integral Particle Separator and Pneumatic Starters, AlliedSignal 36-150[S-92] Auxiliary Power Unit 90 shp w/35 KVA 3-phase AC Generator, Engine Instrument and Caution Advisory System (EICAS), Four Blade Fully Articulated Main Rotor System w/Manual Bladefold Provisions, Dual Controls, 115 Volt 400 Hz AC, 3-phase Electrical System with two 75 KVA Oil Cooled Generators and two 28 Volt DC 400 amp DC Converters, One 28 volt DC 15 Amp-hour Battery, *(Note: This battery is replaced by Option 81002 24 AMP Hour Battery)* Upper Anti-Collision light (strobe), Retractable Landing Gear, 760 Gallons Fuel in two External Sponsons with Self-Sealing Breakaway Valves, Pressure Refueling System,

Pilot and copilot Heated Glass Windshields,
Dual Windshield Wipers w/Washer System,
Exterior Lighting,
Bleed Air Heating and Defogging,
Pilot and Copilot Seats with 5 Point Restraint/Harness,
(Note: These seats are replaced by Option 71007 Crew Seats with Sheepskin seating)
Active Vibration Control System,
Large 6 Ft High by 6 Ft wide by 20 Ft long Cabin Area,
Four (4) cabin emergency exits,
Two (2) cockpit emergency exits,
Hydraulic Cargo Ramp,
Six (6) Exterior Aircraft tiedown fittings.



ADDITIONAL SPECIFICATIONS:

Avionics Management System
Dual Collins VHF-422D
Dual VOR/ILS Collins VIR-432
Dual Mode S Transponder, TDR-94D
Dual DME Collins DME-442
FMS w/ GPS
Primus 880
Digital Moving Map EuroAvionics
EGPWS
TCAS-I
Honeywell JetMap
Life rafts
Emergency Flotation System (EFS)
Air Conditioning System
Rotor Blade Ice Protection System





Contact: George Reenstra 201-995-9570 or George@yourjet.com

Additional information available at www.yourjet.com